


# CEVAC P-Serie

The P-Series is a pumpunit that are equipped with Vacon 100Flow frequency inverter. Prepared for automatic filter cleaning and two pipe cleaning valves as standard.

SD signals can be applied as optional.



0184669328



**FluidTechnics**  
sterk in vloeïend werk

|                                       |        | P-4F/P5,5F<br>400V | P-7F / P-12,5F<br>400V |
|---------------------------------------|--------|--------------------|------------------------|
| Storlek/Size (DxBxH)/LxWxH            | [cm]   | 62x62x140          | 62x62x140              |
| Vikt/Weight (ca.)                     | [kg]   | 80/95              | 110/160                |
| Spänning/Voltage                      | [V]    | 400                | 400                    |
| Strömstyrka/Power                     | [A]    | 9/13,3             | 15/28                  |
| Effekt/Effect                         | [kW]   | 4/5,5              | 7,5/12,5               |
| Luftmängd/Airflow                     | [m³/h] | 550/700            | 850/1400               |
| Vakuum/Vacuum                         | [mbar] | -280               | -280                   |
| Filteryta/Filteraria                  | [m²]   |                    |                        |
| Filtrering/Filtration                 | [%DOP] |                    |                        |
| Dammbehållare/Dust bag                | [l]    |                    |                        |
| Antal samt. Användare/Number of users | -      | 1-3/1-4            | 1-5/1-8                |

\* Max. luftvolym beror på frekvensomriktarens parameterinställning Hz \* Antal användare uträknat med 32mm städustrustning

\* Max airflow depending on parameter setting set Hz \* Number of users are estimated on 32mm cleaning supply.