


FLUIDAxx 40 l/min
 12 V-DC-SK-SK-DM

Item number: 23 632
EAN:
Discount group: D

Technical data

Connection suction side:	quick connecting coupler
Connection discharge side:	quick connecting coupler
Hydraulic data	
Pump design:	axial gear, self-priming
Delivery rate under free discharge up to (l/min) / (gpm):	40 / 10,6
Suction height up to (m) / (ft):	4 / 13,1
Discharge pressure up to (bar) / (psi):	0,8 / 11,6
Flow media:	Fuel oil, diesel, water
Motor data	
Voltage (V):	12 V DC
Power consumption (A):	21
Power (W):	300
Duty cycle (min):	15
Torque (Nm):	0,62
Rotation speed (rpm):	2750
Protection class:	IP 44
Materials of parts in contact with liquid	
Pump housing:	brass
Axial gear:	brass
Dimensions LxWxH (mm) / (inch):	353 x 163 x 110 / 13,9 x 6,4 x 4,3
Weight (kg) / (lb):	7,9 / 17,5

Specification

- sea-water resistant
- integral back-flow valve
- 2 hose inserts with quick connecting coupler
- 3 hose clips DIN 3017, adjustable from 25-40 mm
- Suction filter (23 180)
- Designed for mounting on ceilings (DM)

Special notes

- Materials guarantee a low weight and an exceptional lifetime with optimized efficiency
- For any situation in which a battery is not available, such as construction sites, in agriculture, on boats etc.

Packaging

Dimensions LxWxH (mm) / (inch):	360 x 170 x 210 / 14,2 x 6,7 x 8,3
Weight including package (kg) / (lb):	8,7 / 19,2
Packing unit:	1.0