

**FLUIDAxx 40 l/min**

12 V-DC-SK-SK-WML

**Item number:** 23 633  
**EAN:**  
**Discount group:** D

**Technical data**

Connection suction side: quick connecting coupler  
Connection discharge side: quick connecting coupler  
Hydraulic data  
Pump design: axial gear, self-priming  
Delivery rate under free discharge up to (l/min) / (gpm): 40 / 10,6  
Suction height up to (m) / (ft): 4 / 13,1  
Discharge pressure up to (bar) / (psi): 0,8 / 11,6  
Flow media: Fuel oil, diesel, water  
Motor data  
Voltage (V): 12 V DC  
Power consumption (A): 21  
Power (W): 300  
Duty cycle (min): 15  
Torque (Nm): 0,62  
Rotation speed (rpm): 2750  
Protection class: IP 44  
Materials of parts in contact with liquid  
Pump housing: brass  
Axial gear: brass  
Dimensions LxWxH (mm) / (inch): 353 x 163 x 110 / 13,9 x 6,4 x 4,3  
Weight (kg) / (lb): 7,9 / 17,5

**Specification**

- sea-water resistant
- integral back-flow valve
- 2 hose inserts with quick connecting coupler
- 3 hose clips DIN 3017, adjustable from 25-40 mm
- Suction filter (23 180)
- Designed for left hand wall mounting (WML)

**Special notes**

- Materials guarantee a low weight and an exceptional lifetime with optimized efficiency
- For any situation in which a battery is not available, such as construction sites, in agriculture, on boats etc.

**Packaging**

Dimensions LxWxH (mm) / (inch): 360 x 170 x 210 / 14,2 x 6,7 x 8,3  
Weight including package (kg) / (lb): 8,7 / 19,2  
Packing unit: 1.0