

**FLUIDAxx 40 l/min**

12 V-DC-G 1" male-G 1" male BM

**Item number:** 23 643**EAN:****Discount group:** D**Technical data**

Connection suction side: G 1" male

Connection discharge side: G 1" male

Hydraulic data

Pump design: axial gear, self-priming

Delivery rate under free discharge up to  
(l/min) / (gpm): 40 / 10,6

Suction height up to (m) / (ft): 4 / 13,1

Discharge pressure up to (bar) / (psi): 0,8 / 11,6

Flow media: Fuel oil, diesel, water

Motor data

Voltage (V): 12 V DC

Power consumption (A): 21

Power (W): 300

Duty cycle (min): 15

Torque (Nm): 0,62

Rotation speed (rpm): 2750

Protection class: IP 44

Materials of parts in contact with liquid

Pump housing: brass

Axial gear: brass

Dimensions LxWxH (mm) / (inch): 300 x 170 x 210 / 11,8 x 6,7 x 8,3

Weight (kg) / (lb): 7,7 / 17

**Specification**

- sea-water resistant
- integral back-flow valve
- 3 hose inserts with sealing cone DN 25
- 3 sleeve nuts G 1" female, DN 25
- 3 hose clips DIN 3017, adjustable from 25-40 mm
- Suction filter (23 180)
- For mounting use mounting set (23 690)
- Designed for floor mounting (BM)

**Special notes**

- Materials guarantee a low weight and an exceptional lifetime with optimized efficiency
- For any situation in which a battery is not available, such as construction sites, in agriculture, on boats etc.

**Packaging**

Dimensions LxWxH (mm) / (inch): 360 x 170 x 210 / 14,2 x 6,7 x 8,3

Weight (kg) / (lb): 8,5 / 18,7

Packing unit: 1.0