

DISPENSERS DRUM VISCOMAT

EN. Diesel transfer unit for non commercial use. Easily connected to drums via a quick 2" coupling. Fitted with a telescopic suction tube for direct connection to fuel drums and nozzle housing located above the drum, near the pump, for easy, clean operations. Fitted with mechanical meters to ensure precise dispensing and control of single user consumption.

ES. Grupo de trasiego de gasóleo para uso privado. Fácil de conectar al bidón mediante conexión rápida de 2". Se suministra con tubo telescópico en aspiración para conectar directamente al bidón y con alojamiento para la pistola situado en las proximidades de la bomba, sobre el bidón, para consentir un uso fácil y limpio del surtidor. Dispone de un cuentalitros mecánico que permite efectuar suministros precisos y administrar el consumo de los distintos usuarios.

PT. Grupo de transferência de gasóleo para uso particular. Fácil de coligar a um tambor mediante um engate rápido de 2". Equipados com tubo telescópico na aspiração para coligar-se directamente ao tambor e com compartimento para guardar a pistola perto da bomba, sobre o tambor, para facilitar a utilização e a limpeza do distribuidor. São equipados com contador de litros mecânico para efectuar abastecimentos com precisão e para a gestão do consumo dos utilizadores individualmente

PERFORMANCE

- AC and DC versions available
- Flow rate up to 25 l/min

- Disponible en versión CA y CC
- Caudal hasta 25 l/min

- Disponível na versão AC e DC
- Caudal até 25 l/min

PRODUCTS' RANGE WEIGHT AND PACKAGING

Code	Weight		Packaging		
	kg	lbs	mm	inch	pcs/box
F0026102D	18	39,6	480x370x265	18,9x14,6x10,4	1
F0026100D	18	39,6	480x370x265	18,9x14,6x10,4	1
F0026200D	18	39,6	480x370x265	18,9x14,6x10,4	1
F00268000	9	19,8	357x357x275	14,1x14,1x10,8	1
F00268010	9	19,8	480x370x265	18,9x14,6x10,4	1
000270000	18	39,6	480x370x265	18,9x14,6x10,4	1
000270010	21	46,3	500x380x280	19,7x15x11	1



Flow-rate
up to
25 l/min
(up to 7 gpm)

Accuracy
+/-
0,5 %

Viscosity
up to
2000 cSt



DISPENSERS

PUMPS

METERS

NOZZLE METERS

NOZZLE

SPECIAL EQUIPMENTS

FLUID MONITORING

ACCESSORIES

FILTERING



FEATURES

ON REQUEST

Ergonomic nozzle
(DC models)

Foot valve
(DC models)

Kit cable

Ergonomic nozzle
(AC models)

Extensible pipe
(AC models)

Mechanical meter

PRODUCTS' RANGE TECHNICAL DATA										
Code	Description	Fluids	Flow-rate		Voltage			Pump	Nozzle	Hoses lenght
		type	l/min	gpm	AC V./Hz DC Volt	Power Watt	Amp. max.			
F0026102D	DRUM Viscomat 200/2 110V/60HZ		9	2	110	1500	15	DC Viscomat 200/2	Easyoil	4
F0026100D	DRUM Viscomat 200/2 230V/50-60HZ		9	2	230-50/60	800/950	3,8/4,6	DC Viscomat 200/2	Easyoil	4
F0026200D	DRUM Viscomat 200/2 230V/50/60HZ K400		9	2	230-50/60	800/950	3,8/4,6	DC Viscomat 200/2	K400	4
F00268000	DRUM Viscomat 60/1 12V		4	1,2	12	150	18,5	AC Viscomat 60/1	Easyoil	4
F00268010	DRUM Viscomat 60/1 24V K400		4	1,2	24	150	18,5	AC Viscomat 60/1	K400	4
000270000	DRUM Viscomat 70M		28	7	230	750	4,6	AC Viscomat 70 M	Self3000	4
000270010	DRUM Viscomat 70M K33		25	7	230	750	4,6	AC Viscomat 70 M	Self3000	4

The units can also be supplied for operating under different voltages and with meter.