

S MANUAL NOZZLES SELF



EN. Manual nozzles. These nozzles, distinguished by high efficiency, based on low flow resistance, remarkably easy use and of reasonable cost, are designed to be used with any type of transfer system, even those run by gravity. Supplied complete with removable lever protection, a variety of threaded connectors and a reduced section tube for unleaded gasoline.

ES. Pistolas manuales. Se caracterizan por su eficiencia y la resistencia en caudal bajo, facilidad de uso y precio económico. Dadas sus características, encuentran fácil instalación en todo tipo de instalaciones de trasiego, incluso en las que funcionan con gravedad. Se proveen completos con protección de palanca removible, una variedad amplia de enrosques de para diferentes conexiones u tubo de sección reducida para la gasolina.

PT. Pistolas manuais. Caracterizam-se por uma alta eficiência por causa da baixa resistência ao fluxo juntamente com uma notável simplicidade na utilização e economia. Por causa das suas características, podem ser aplicadas em qualquer tipo de sistema de transferência, mesmo os que funcionam por gravidade. São fornecidas equipadas com bloqueio do gatilho, que pode ser solto, e são disponíveis com vários engates com rosca e com tubo de pequeno diâmetro para gasolina verde.

PERFORMANCE

Flow rate up to 150 l/min

Caudal de hasta 150 l/min

Caudal até 150 l/min



PRODUCTS' RANGE WEIGHT

Code	Weight	
	kg	lbs
F00641130	0,7	1,5
F0065000A	0,6	1,3
00065001A	0,6	1,3
F0063001A	0,2	0,4
F0063000A	0,2	0,4

NOZZLE

ANTIFREEZE

BIO DIESEL

DIESEL

FOOD

GASOLINE

GREASE

KEROSENE

OIL

UREA

WATER

WINDSCREEN

Flow-rate
up to
150 l/min
(up to 40 gpm)



DISPENSERS

PUMPS

METERS

NOZZLE METERS

NOZZLE

SPECIAL EQUIPMENTS

FLUID MONITORING

ACCESSORIES

FILTERING



SELF 2000 DIESEL



SELF 3000 DIESEL/GASOLINE



PLASTIC NOZZLE-S WATER/DIESEL



PLASTIC NOZZLE WATER/FOOD

FEATURES



Swivel

Not included in the Plastic nozzle model



UREA NOZZLE (available)

PRODUCTS' RANGE TECHNICAL DATA

Code with swivel	Description	Fluid type	Flow-rate		Inlet		Spout ext. Ø mm
			l/min	gpm	swivel BSP	with swivel BSP	
F00641130	* Self 2000 1"	B D G O	120	32	YES	F 1"	0,7
F0065000A	* Self 3000 1"	B D G O	150	40	YES	F 1"	0,6
00065001A	* Self 3000 1" unleaded spout	B D G O	150	40	YES	F 1"	0,6
F0063001A	Plastic nozzle 1" (water/food version)	B D G O W	80	21	NO (Hose tail 1")	F 1"	0,2
F0063000A	Plastic nozzle-S 1"	B D G O W	80	21	YES	F 1"	0,2