

FILTROS DOMÉSTICOS RESIDENTIAL FILTERS



DESCRIPCIÓN

FILTROS DOMÉSTICOS EN POLIÉSTER LAMINADO SERIE BALEAR

Filtros KRIPSOL, de poliéster laminado, color rojo metalizado. Incluyen: manómetro, válvula selectora lateral de 6 vías: V6.43B de 1 1/2" o V6.63B de 2" con enlaces (modelos BR/BL) o válvula Top 6 vías V6T.41B (modelos BT).

Velocidad de filtración: 50 m³/h / m².

Presión máxima: 1,6 Kg/cm².

Presión de trabajo: 0,5 - 1,3 Kg/cm².

Presión de prueba: 2,5 Kg/cm².

Temperatura de trabajo: 1° C ÷ 50° C.

Granulometría de arena: 0,4 ÷ 0,8 mm.

DESCRIPTION

FILTERS FOR RESIDENTIAL POOLS MADE IN LAMINATED POLYESTER BALEAR SERIES

KRIPSOL filters, made in laminated polyester, metallized red colour, including pressure gauge, 6 ways side valve: V6.43B-1 1/2" or V6.63B- 2" with connection to filter (BR/BL models) or 6 ways TOP valve V6T.41B (BT models).

Filtration speed: 50 m³/h / m².

Maximum pressure: 1,6 Kg/cm².

Working pressure: 0,5 - 1,3 Kg/cm².

Testing pressure: 2,5 Kg/cm².

Operating temperature: 1° C ÷ 50° C.

Sand grading: 0,4 ÷ 0,8 mm.



MODELO BR640
BR640 MODEL

MODELO BR, TAPA NEGRA ATORNILLADA / BR MODEL, BOLTED BLACK LID

MODELO MODEL	CÓDIGO ITEM NR.	FILTRO Ø mm. FILTER	CAUDAL m ³ /h FLOW	(*) S. F. m ² F. A.	CONEXION Ø mm. CONNECTION	PESO kg. WEIGHT	VOLUM. m ³ VOLUME	UDS. Caja/Box QTY.
BR 400.C	021040103401	400	6	0,13	1 1/2"	11,5	0,127	1
BR 450.C	021045103401	450	8	0,16	1 1/2"	14,0	0,158	1
BR 520.C	021052103401	520	10	0,21	1 1/2"	17,0	0,242	1
BR 640.C	021064103401	640	15	0,32	1 1/2"	23,0	0,366	1
BR 680.C	021068203401	680	18	0,36	2"	26,0	0,426	1
BR 760.C	021076203401	760	22	0,45	2"	34,0	0,608	1
BR 900.C	021090203401	900	30	0,63	2"	45,0	0,902	1

(*) S.F.: Superficie Filtración F.A.: Filtration Area

MODELO BL, TAPA TRANSPARENTE ROSCADA / BL MODEL, TRANSPARENT THREADED LID


MODELO MODEL	CÓDIGO ITEM NR.	FILTRO Ø mm. FILTER	CAUDAL m ³ /h FLOW	(*) S. F. m ² F. A.	CONEXION Ø mm. CONNECTION	PESO kg. WEIGHT	VOLUM. m ³ VOLUME	UDS. Caja/Box QTY.
BL 400.C	021240107401	400	6	0,13	1 1/2"	11,5	0,127	1
BL 450.C	021245107401	450	8	0,16	1 1/2"	14,0	0,158	1
BL 520.C	021252107401	520	10	0,21	1 1/2"	17,0	0,242	1
BL 640.C	021264107401	640	15	0,32	1 1/2"	23,0	0,366	1
BL 680.C	021268207401	680	18	0,36	2"	26,0	0,426	1
BL 760.C	021276207401	760	22	0,45	2"	34,0	0,608	1
BL 900.C	021290207401	900	30	0,63	2"	45,0	0,902	1

(*) S.F.: Superficie Filtración F.A.: Filtration Area



MODELO BL640
BL640 MODEL

0184669328



FluidTechnics
sterk in vloeierend werk