DISPENSERS

SELF SERVICE MC for AdBlue®

MADE IN ITALY

EN. New AdBlue® dispenser for non-commercial use. Sturdy structure fitted with front panel for easy maintenance. Diaphragm pump is equipped with an electric motor that has no need for a dynamic seal. This solution forms the basis for the production of a reliable industrial pump with self-priming capabilities. The Self Service MC also comes with our SB325 automatic nozzle with break-away system and stainless steel spout and the AdBlue® 3D Filter.

Equipped with turbine-type digital flow meter and electronic unit for multi-user consumption, management, and pre-selected dispensing. Local memory of the last 255 events. PC interface for exporting and organizing data. Capability of entering vehicle registration number, mileage, date and time of delivery. Magnetic keys (keys kit) available for user recognition.

On request: dedicated software for printing individual summaries of dispensing details.

ES. *Nuevo surtidor de AdBlue® para uso privado. Estructura robusta con puerta frontal para facilitar el mantenimiento. Bomba de membrana dotada de motor eléctrico sin juntas dinámicas. Esta solución permite obtener una bomba industrial fiable y autocebante. Pistola automática SB325 con sistema Break-Away y caño de acero inoxidable. FILTRO 3D para AdBlue®.*

Cuentalitros digital de turbina, centralita electrónica para preselección y gestión multiusuario de los consumos. Memoria local capaz de almacenar las últimas 255 operaciones. Interfaz con PC para la exportación y organización de los datos. Posibilidad de introducir el código del vehículo, el kilometraje, la fecha y la hora del suministro. Disponibilidad de llaves magnéticas (Kit keys) para el reconocimiento de los usuarios.

A petición: software específico para imprimir informes detallados de los suministros discriminados por usuario.

PT. Novo distribuidor para AdBlue® de uso privado. Estrutura robusta equipada com portinha dianteira para facilitar a manutenção. Bomba com membrana e motor elétrico sem equipamentos dinâmicos. Esta solução permite obter uma bomba industrial confiável com capacidade de disparo automático. Pistola automática SB325 com sistema Break-Away e bico em aço inoxidável. FILTRO 3D para AdBlue®.

Com controles digitais de turbina e central eletrônica de pré-seleção e gestão de vários usuários de consumos. Memória local das últimas 255 operações. Interface com PC para exportação e organização dos dados. Possibilidade de introduzir código da viatura e quilometragem, data e hora do abastecimento.
Há disponíveis chaves magnéticas (Kit keys) para reconhecer os utilizadores.

A pedido: software dedicado com possibilidade de imprimir pormenores dos abastecimentos e sumários por utilizador.

PERFORMANCE

- Flow rate up to 34 l/min
- Accuracy: +/- 1 %
- Duty cycle 20 min
- IP55 protection

- *Caudal hasta 34 l/min*
- *Precisión de cálculo: +/- 1 %*
- *Ciclo de trabajo 20 min*
- *Protección IP55*

- Carga de até 34 l/min
- Precisão: +/- 1 %
- Ciclo de trabalho de 20 min
- Proteção IP55

DIMENSIONS

COLUMN VERSION



Hose:
- length 6 m
- Ø 3/4"

PRODUCTS' RANGE WEIGHT AND PACKAGING

Code	Weight		Packaging		
	kg	lbs	mm	inch	pcs/box
Column versions					
F00744000	50	110	1478x488x400	58,2x10,2x16,5	1

Flow-rate up to **34** l/min (up to 9 gpm)

Accuracy +/- **1%**

Users no. **80** max.

PIUSI

Column version

ON REQUEST

Self service desk software

See “Fluid monitoring” section

User key

Code **R15904000**
Composed by 10 User yellow key

FEATURES

AdBlue® long life 3D Filter

Code F00611D10

Display cover

Nozzle SB325

Code F00617510

PRODUCTS’ RANGE TECHNICAL DATA

Code	Description	Fluids	Flow-rate		Voltage			Meter	Nozzle	Filter	Inlet	PC
		type	l/min	gpm	AC V./Hz DC Volt	Power Watt	Amp. max.	mod.	type	3D filter	BSP	connection
Column versions												
F00744000	Self service 70 MC for AdBlue®	U	34	9	230/50	400	1,95	K24	SB325	YES	3/4”	YES

Upon request it is available with different voltages and 60 Hz frequency