









E140

FEATURES

- · CONTINUOUS DUTY
- HIGH FLOW-RATE
- HEAVY DUTY PUMP
- STURDY DESIGN

The E14O diesel transfer pump is versatile and suitable for different industries including automotive, agriculture, transportation, garages and construction. The E14O volumetric, self-priming vane pump for diesel transfer has a high seal and is reliable in conditions of use at low temperatures. With its solid and resistant body, the E14O is an easy to install diesel transfer pump, suitable for use in diesel dispensers and fixed fuel transfer systems, as well as other industrial applications. The compact cast iron structure makes the E14O electric pump the perfect system for performance and reliability.

PERFORMANCE

ир то **140 L/MIN**

FLOW RATE

AC VOLTAGE POWER





E140

PACKAGING													
CODE	WEIGHT		F	N. BOXES / EUROPALLET									
	KG	LBS	ММ	INCH	PCS/BOX	×	•						
F00395050	18	40	350X250X300	14X1OX12	1	60	72						



































IN THE BOX


- E140 PUMP
- · INSTRUCTION MANUAL


DETAILS





DIMENSIONS





Dimensions expressed in millimeters

MATERIALS

- BODY: CAST IRON
- ROTOR: SINTERED STEEL
- · VANES: TECHNOPOLYMER
- SEAL: VITON
- SHAFT: STEEL

TECHNICAL DATA										
CODE	DESCRIPTION	FLUIDS TYPE	FLOW-RATE		VOLTAGE			DUTY CICLE		INLET
			L/MIN	GPM	AC VOLT/HZ	POWER WATT	AMP. MAX.	CONTINUOUS	RPM	BSP
F00395050	E 14O 23O/5O	D	140	37	230/50	1150	5	S1	1450	1" 1/4



